

# ECOCELL

with natural air convection, 250 °C



**MMM**  
Medcenter  
Einrichtungen GmbH

MMM-Group



The highly cost-effective heating oven series for simple drying processes. The ECOCELL-line produces no noise and provides a very soft air convection within the chamber.

**Volume:**

55, 111, 222, 404, 707 litres

**Working temperature:**

5 °C above ambient temperature up to 250 °C

**Interior:**

stainless steel, mat. No. 1.4301 (AISI 304)

## The versatile standard line with microprocessor control unit

- 3 programs
- RS 232- interface for printer or PC-communication
- delayed heating start and stop function
- acoustic alarm
- time range 99 hours 59 minutes
- mechanic safety thermostat class 2



## Options

- door window and interior lighting
- access ports Ø 25, 50, 100 mm
- door lock
- left door versions (excluded volume 707 litres)
- separate PT 100-sensor and display
- communication software for PC (Windows)

# ...standard line

## The high-tech comfort line with multi-functional microprocessor control unit

- 6 programs
- chip card system for individual program storage
- RS 232- interface for printer or PC-communication
- delayed heating start and stop function
- acoustic alarm
- time range 0-16 years with 1 min-intervals
- digital safety thermostat class 3
- real time
- programming temperature ramps
- heating sequences
- programme cycles



## Options

- door window and interior lighting
- access ports Ø 25, 50, 100 mm
- door lock
- left door versions (excluded volume 707 litres)
- communication software for PC (Windows)
- potential-free alarm contact
- independent temperature measuring through PT 100 sensor (with indication on LCD display or PC)

# ...comfort line

Technical data		Models	55	111	222	404	707
Interior of stainless steel material No. 1.4301	volume	cca ltrs	55	111	222	404	707
	width	cca mm	400	540	540	540	940
	depth	cca mm	390	390	540	540	540
	height	cca mm	350	530	760	1410	1410
Tray	racks	max. No.	4	7	10	19	19
	standard equipment	pcs. included	2	2	2	2	2
Maximal weight of the load*)	per tray	max. kg	20	20	30	30	50
	inside the oven	max. kg	50	50	70	100	130
Door		No.	1	1	1	1	2
External dimensions (including door and handle)	width	cca mm	620	760	760	760	1160
	depth	cca mm	640	640	790	790	790
	height (incl. Foot and Rolls)	cca mm	680F	860F	1100F	1910R	1910R
	diameter of the air branch outer/inner	cca mm	52/49	52/49	52/49	52/49	52/49
Package dimensions (three layers carton)	width	cca mm	710	850	850	850	1250
	depth	cca mm	720	730	730	860	910
	height (incl. palette)	cca mm	900	1080	1320	2150	2150
Mass	net	cca kg	55	75	100	150	215
	brut	cca kg	61	84	117	165	233
Working temperature (beginning of the regulation)		from 5 °C above ambient temp. to °C	250	250	250	250	250
Temperature accuracy according to DIN 12 880 T2, at working temperature with closed air flap and door	space deviation	cca ± % of the reached temperature	2	2	2	2,5	3,5
	time variation	cca ± °C	0,3	0,3	0,3	0,3	0,3
Time required to reach 250 °C with closed air flap and voltage 230 V		cca min.	59	60	99	85	95
Heat emission at 250 °C		cca W	590	760	990	1940	2550
Air exchange speed at 150 °C		cca/hour	8	12	5	4	3
Electricity - mains 50/60 Hz	max. power input	cca kW	1,3	1,9	1,8	3,6	4,5
	stand by	cca W	5	5	5	5	5
	current	A	5,6	8,3	7,8	3,9; 3,9; 7,8	3,9; 7,8; 7,8
	nominal voltage	V	230	230	230	400/3N	400/3N

\*) Approx. 50 % of the tray area can be filled in a way a uniform air circulation is enabled inside the chamber.

Note: All technical data are related to 22 °C ambient temperature and ± 10 % voltage swing (if not specified). Changes in the design and make reserved.



**MMM**  
Medcenter  
Einrichtungen GmbH

MMM-Group

MMM Medcenter  
Einrichtungen GmbH  
Schulstrasse 29  
D-82166 Gräfelfing / München

tel.: +49 89 89 92 26 20  
fax: +49 89 89 92 26 30  
e-mail: [medcenter@mmmgroup.com](mailto:medcenter@mmmgroup.com)  
<http://www.mmm-medcenter.com>